

# Eaton 5S UPS

550/700/1000/1500VA



Eaton 5S UPS product range



Eaton 5S versatility

## Ideal for protecting:

- Workstations
- Business Telephony
- Network devices
- Point-of-sale equipment



## Affordable power protection for workstations

### Performance

- The Eaton 5S UPS provides effective power protection, even in disturbed electrical environments. Voltage fluctuations are automatically corrected using an AVR device (booster/fader), without needing the batteries.
- The 5S not only provides a supply with battery backup to keep equipment operating during power cuts, but also provides effective protection against damaging surges.

### Reliability

- The 5S protects networked equipment from “back door” power surges coming through Ethernet, internet or telephone lines.
- The 5S’s periodic automatic battery testing ensures early detection if a battery needs to be replaced.
- The easy-to-replace battery helps to extend the UPS service life.

### Versatility

- The 5S can be installed vertically over or under a desk, or horizontally under a screen. Its compact, slimline form factor even allows it to be easily integrated into environments with space constraints.
- The 5S features an HID-compliant USB port, for automatic integration with common operating systems (Windows/ Mac OS/Linux). The 5S is also compatible with Eaton UPS Companion power management software.
- All models come bundled with a USB cable and two IEC-IEC load cables.

# EATON

Powering Business Worldwide

# Eaton 5S UPS

- 1 LED user interface
- 2 Battery replacement panel
- 3 USB port



- 4 Data line protection
- 5 4 IEC 10A and 4 surge only IEC 10A
- 6 Circuit breaker reset button

Eaton 5S 1000i UPS

| TECHNICAL SPECIFICATIONS  | 550   | 700               | 1000              | 1500              |
|---|---|-------------------|-------------------|-------------------|
| Rating (VA/W)   | 550 VA / 330 W  | 700 VA / 420 W    | 1000 VA / 600 W   | 1500 VA / 900 W   |
| <b>Electrical Characteristics</b>   |   |                   |                   |                   |
| Technology  | Line-Interactive (AVR with Booster + Fader)   |                   |                   |                   |
| Input voltage range   | 175V-275V   |                   |                   |                   |
| Output voltage  | 230 V   |                   |                   |                   |
| Frequency   | 50-60 Hz autoselect   |                   |                   |                   |
| <b>Connections</b>  |   |                   |                   |                   |
| Number of IEC outlets   | 4   | 6                 | 8                 | 8                 |
| Outlets with surge protection and backup /<br>Outlets with surge protection | 3/1   | 3/3               | 4/4               | 4/4               |
| <b>Batteries</b>  |   |                   |                   |                   |
| Typical backup times at 50 and 70% load*                                    | 10/6 mn   | 9/5 mn            | 14/8 mn           | 11/8 mn           |
| Battery management  | Automatic battery test, deep-discharge protection, cold-start capable, replaceable batteries  |                   |                   |                   |
| <b>Communication</b>  |   |                   |                   |                   |
| Communication Port  | HID-compliant USB port for automatic integration with most common operating systems (Windows Vista, 7 & 8, Linux, Mac OS X), cable supplied |                   |                   |                   |
| Data line protection  | Tel/Fax/Modem/Internet and Ethernet   |                   |                   |                   |
| <b>Standards</b>  |   |                   |                   |                   |
| Safety & EMC  | IEC/EN 62040-1, IEC/EN 62040 -2, CB Report, CE mark   |                   |                   |                   |
| <b>Dimensions &amp; Weight</b>  |   |                   |                   |                   |
| Dimensions H x W x D  | 250 x 87 x 260 mm   | 250 x 87 x 260 mm | 250 x 87 x 382 mm | 250 x 87 x 382 mm |
| Weight  | 4.96kg  | 5.98kg            | 9.48kg            | 11.08kg           |
| <b>Customer Service &amp; Support</b>                                       |   |                   |                   |                   |
| Warranty  | 2 years warranty including batteries  |                   |                   |                   |

\* Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

| Part Numbers | 550    | 700    | 1000    | 1500    |
|--------------|--------|--------|---------|---------|
| 5S           | 5S550i | 5S700i | 5S1000i | 5S1500i |

In the interests of continuous product improvement, all specifications are subject to change without notice.

